



WATER SOFTENER CHART

Vat volume	1) Level of water hardness detected in water (as ppm CaCO ₃ equivalent)												
	40ppm	50ppm	100ppm	200ppm	250ppm	300ppm	400ppm	500ppm	600ppm	700ppm	800ppm	900ppm	1,000ppm
	2) mL of Raynox Water Softener to add into vat.												
100L	30	40	80	160	200	230	310	390	470	550	620	700	780
400L	120	160	310	620	780	940	1,250	1,560	1,870	2,180	2,500	2,810	3,120
1000L	310	390	780	1,560	1,950	2,340	3,120	3,900	4,680	5,460	6,240	7,020	7,800
1500L	470	590	1,170	2,340	2,930	3,510	4,680	5,850	7,020	8,190	9,360	10,530	11,700
2000L	620	780	1,560	3,120	3,900	4,680	6,240	7,800	9,360	10,920	12,480	14,040	15,600
2270L (500gallons)	710	890	1,770	3,540	4,430	5,310	7,080	8,850	10,620	12,390	14,160	15,940	17,710

To confirm the correct amount of water softener has been added, we recommend a jar test with Raynox be carried out at water hardness above 100ppm.

If in any doubt as to the correct amount of water softener to add, contact:

Colin Campbell (Chemicals) Pty Ltd
 Telephone : (02) 9725 2544
 Fax : (02) 9604 7768
 Email : cccsyd@campbellchemicals.com.au